

## TUBI S.S. TRAFILATI A FREDDO PER SCAMBIATORI DI CALORE

D.E.		SERIE SPESSORI SECONDO SCALA BWG – AVERAGE WALL – (SPESS. MEDIO)											
DIAM (INC)	(mm)	8	9	10	11	12	13	14	15	16	17	18	19
		4,191	3,759	3,403	3,048	2,768	2,413	2,108	1,828	1,651	1,473	1,244	1,066
		PESO METRICO (kg/mt)											
5/8"	15,875		1,123	1,047	0,964	0,895	0,801	0,716	0,633	0,579	0,523	0,449	0,389
3/4"	19,05		1,417	1,313	1,203	1,111	0,99	0,881	0,776	0,708	0,638	0,546	0,473
1"	25,4	2,192	2,006	1,846	1,68	1,545	1,368	1,211	1,063	0,967	0,869	0,741	0,64
1 1/4"	31,75	2,848	2,595	2,379	2,157	1,978	1,746	1,541	1,349	1,225	1,1	0,936	0,807
1 1/2"	38,1	3,504	3,183	2,912	2,635	2,412	2,124	1,871	1,635	1,484	1,33	1,131	0,974
2"	50,8	4,817	4,361	3,977	3,589	3,279	2,879	2,531	2,208	2,001	1,792	1,52	1,307

D.E.		SERIE SPESSORI SECONDO SCALA BWG – MINIMUM WALL – (SPESS. MINIMO)											
DIAM (INC)	(mm)	8	9	10	11	12	13	14	15	16	17	18	19
		4,191	3,759	3,403	3,048	2,768	2,413	2,108	1,828	1,651	1,473	1,244	1,066
		PESO METRICO (kg/mt)											
5/8"	15,875		1,197	1,12	1,035	0,963	0,865	0,775	0,687	0,63	0,57	0,49	0,425
3/4"	19,05		1,521	1,413	1,298	1,202	1,073	0,957	0,845	0,772	0,696	0,597	0,517
1"	25,4	2,364	2,168	1,999	1,823	1,679	1,489	1,32	1,16	1,056	0,95	0,811	0,701
1 1/4"	31,75	3,085	2,816	2,585	2,348	2,155	1,904	1,683	1,475	1,341	1,204	1,025	0,884
1 1/2"	38,1	3,807	3,463	3,171	2,873	2,632	2,32	2,046	1,79	1,625	1,458	1,239	1,068
2"	50,8	5,251	4,758	4,344	3,923	3,586	3,151	2,772	2,419	2,194	1,965	1,668	1,435